

# Grease Guardian<sup>®</sup>

## D Range

*"My mind is at rest  
with Grease Guardian"*

MARK SIMMONS  
CHEF

### GREASE REMOVAL UNIT (UNDERSINK)



- Traps grease & foodwaste
- Removes grease automatically
- Reduces pump out requirements
- Robust stainless steel construction
- Easy to install and maintain
- Protects drains (point of source)
- Collected waste can be recycled
- Programmable digital controls
- Tested and approved internationally
- No enzymes or bacteria dosing needed





## THREE-STAGE OPERATION SYSTEM

### STAGE 1 Solids Collection


Wastewater from the kitchen is directed through the inlet of the **Grease Guardian**® where a removable strainer basket collects any solid debris.

### STAGE 2 Grease & Oil Separation

Grease in the wastewater floats to the surface and is trapped while the clear water leaves the unit and enters the drainage system.

### STAGE 3 Self Cleaning & Grease Removal

The timer-driven heating element is activated to liquefy grease, which is then removed by the skimming wheel and deposited into a portable container for recycling. Can be connected to: pot wash sinks, pre-rinse sinks, combi ovens, Chinese cookers and floor drains.



Model	Length (A) INCLUDES INLET & OUTLET	Width (B) MAIN TANK	Width (C) INCLUDING GREASE COLLECTION CONTAINER	Height (D) WITH LID CLOSED CLEARANCE NEEDED	Basket (E) CLEARANCE NEEDED	Inlet/Outlet (F)	Max Flow
<b>D1</b>	643	309	515	326	174	60	0.75l/s
<b>D2</b>	723	309	515	415	212	60	1.25 l/s
<b>D3</b>	812	309	515	453	290	90	1.75 l/s
<b>D4</b>	925	309	515	453	260	115	2.25 l/s

All dimensions in mm.

All drawings in this brochure are guidelines and are subject to change. Always request the latest drawings from your suppliers or visit [www.greaseguardian.com](http://www.greaseguardian.com).

Specification: Automatic grease trap with inbuilt grease skimming mechanism. 16 Gauge 304 Stainless Steel, 25 watt motor, 600 W heater D1-D2; 1.0kw heating element D3-D4. Programmable digital timer, 230V 50Hz as standard. 110V 60Hz also available. Each wheel skims 2kg of free floating grease per hour. Left-to-right or right-to-left handling of unit to suit preferred flow direction.

**For invert levels please contact your local supplier.**



#### Manufacturers

FM Environmental  
Greenbank Industrial Estate  
Newry BT34 2QX  
Northern Ireland  
T: +44(0)28 302 66616  
F: +44(0)28 302 63233  
E: [sales@greaseguardian.com](mailto:sales@greaseguardian.com)  
[www.greaseguardian.com](http://www.greaseguardian.com)

#### Malta

FM Environmental (Malta) Ltd  
Water Technology House  
A15B Industrial Estate  
Marsa, Malta  
T: +356 2122 6172  
F: +356 2122 6171  
E: [fmmalta@fmenvironmental.com](mailto:fmmalta@fmenvironmental.com)  
[www.fmenvironmental.com](http://www.fmenvironmental.com)

Authorised distributor:

